

PORTABLE X-RAY SYSTEM



- Most compact size and lightest weight
- Provide high resolution imaging at lower dosages
- Durable design with solid body
- Soft Touch Controls with Digital displays
- Calibrated cassette size indicator dials
- Available with Inverted control panel for table use
- Two stage dynamic, Auto line compensation
- Easy access to DR systems
- Dual Integrated Laser Pointer
- Wireless/Wire PC interface (Option)



PORTABLE X-RAY SYSTEM

	BP-2400	BP-2800	BP-3200	BP-4000	BP-5000
Max Output Power	2.4kW	2.8kW	3.2kW	4kW	5kW
Generator Frequency	70kHz	70kHz	70kHz	70kHz	70kHz
kV Range	40~100kV	40~120kV	40~100kV	40~110kV	50~110kV
mA Range	16~40mA	12~40mA	25~60mA	20~80mA	20~100mA
mAs Range	0.4~100mAs	0.4~100mAs	0.4~100mAs	0.4~100mAs	0.4~100mAs
Focal Spot	1.2mm*1.2mm	1.2mm*1.2mm	2.0mm*2.0mm	1.8mm*1.8mm	1.8mm*1.8mm
Target Angle	16°	16°	16°	15°	15°
Anode Heat Storage	50kHU	50kHU	40kHU	42kHU	42kHU
Input Voltage	110V/220V	110V/220V	200V~240V	200V~240V	200V~240V
Phase/Frequency	Single/50~60Hz	Single/50~60Hz	Single/50~60Hz	Single/50~60Hz	Single/50~60Hz
Dimension(mm)	360*200*190	360*200*190	360*200*190	360*200*190	360*200*190
Packing Size(mm)	520*400*330	520*400*330	520*400*330	520*400*330	520*400*330
Net weight	11kG	12kG	12kG	12kG	12kG
G-weight	22kG	22kG	22kG	22kG	22kG

