

AUTOELEX[®]



Care Cradle
RADLE
The Cradle of Pet Care

© 2022. Autoelex Co.,LTD. All rights reserved.



CURADLE SERIES

We, Autoelex Co., Ltd has the utmost and finest technology in our fields through the quality management and technology innovation. Also, we are recognized as the premium Brand by Americans, Japanese, Europeans, Australians, who have the advanced technology.

We, CURADLE delivers emotions of loving life to dear people in over 30 countries right at this moment with our sensible technology which can hold beautiful and happy memories.

We will keep putting our utmost effort so that our loving warmth of 37.5 degrees can be in everywhere.



CURADLE PET BROODER

The Curadle Pet Brooder is a smart pet care house that allows users to control its internal temperature and humidity. It serves as a warm home for the entirety of a pet's life – from infancy to old age. The product is a steady seller that has demonstrated progressive growth in the global market.



CURADLE PET O₂ BROODER

The Curadle Pet O₂ Brooder is a premium pet oxygen chamber that utilizes an artificial intelligence control system that regulates oxygen concentration. Having received international safety certifications, it is a trustworthy product that can adjust the temperature, oxygen concentration by up to 40%.

CURADLE SMART PET INCUBATOR


The Curadle Smart Pet Incubator aids in the recovery of animal patients by accurately regulating temperature, humidity, oxygen concentration, and carbon dioxide concentration.

The pet ambulance model made exclusively for pets provides first aid while on the move. It uses vibration reduction technology built-in to avoid shaking.

The smart pet incubator enables the patients to receive the necessary treatment while being transported.



* KONKUK UNIVERSITY VETERINARY MEDICAL TEACHING HOSPITAL
Pet Ambulance



A smart pet care house that is
the first of its kind in the whole world
CURADLE Pet Brooder




PET BROODER




Large FND display is Easy-to-use menu options, enable optimal environment setting according to the health condition of animal patient.

Nebulizer and Oxygen tank can be connected and used separately or simultaneously



PET BROODER 60 (Capacity 60L)



PET BROODER 90 (Capacity 90L)

SPECIFICATION

Name	CURADLE PET BROODER 60	CURADLE PET BROODER 90
Model NO.	MX-B60N	MX-B90N
Temp. Control	Ambient temperather ~ MAX. 38℃ / ~ 100°F	
External environment temp.	Optimum range 20 ~ 25℃ / 68 ~ 77°F	
Humi. Control	40 ~ 60% (It can be changed according to the conditions)	
External environment humi.	40 ~ 60%	
Power	AC100-120V, 50/60Hz / AC220-240V, 50/60Hz	
Power consumption	Average: 80W / MAX: 150W	Average: 90W / MAX: 150W
size	W 655 x L 470 x H 440mm	W 855 x L 470 x H 440mm
Weight	9kg	10kg

Sold separately

- Build Rack
- Secondary tray
- Stainless steel mesh



Interior



Water cap & water nipple



Oxygen & Nebulizer Sockets



LED lighting

- A centralized heating method offers an environment suitable for pets, newborn animals, and pregnant animals
- An AI alarm system notifies you of temperature stranged
- An AI alarm system notifies you of humidifying water deficiency
- Equipped with a dedicated nebulizer fan to enhance the effects of the treatment.
- Clean Air-filter which removes indoor dust
- An easy-to-clean detachable tray and sliding window
- An anion function provides refreshing effect
- Reduces power consumption by up to 40%
- A secondary tray can be attached inside as a litter box for cats, a birthing box, etc. (option: Secondary tray)
- It is possible to stack machine which enable to provide space efficiency (option: Build Rack)

* This product requires a separate oxygen tank or oxygen concentrator or nebulizer.



Premium Oxygen Room for pets

CURADLE Pet O₂ Brooder




PET O₂ BROODER

O₂

Has oxygen concentration and temperature indicators that enable optimal environment settings

BLDC Fan is embedded in the incubator to control indoor-environment



PET O₂ BROODER 90 (Capacity 90L)

SPECIFICATION

Name	CURADLE PET O ₂ BROODER 90
Model NO.	MX-B90NO2
Temp. Control	Ambient temperature. ~ MAX. 38°C / ~ 100°F
External Environment temp.	Optimal range : 20 ~ 25°C / 68 ~ 77°F
Oxygen concentration Control	21, 25 ~ 40%
Oxygen Supply Pressure	Oxygen tank: 1 ~ 1.5bar is recommended but does not exceed 3bar Oxygen Concentrator: In case of below 6LPM, supply pressure doesn't matter. In case of more than 6LPM, 1 ~ 1.5bar is recommended but does not exceed 3bar
Power	AC100-120V, 50/60Hz / AC220-240V, 50/60Hz
Power consumption	Average: 90W / MAX: 150W
size	W 855 x L 470 x H 440mm
Weight	10kg



Sold separately

- Ringer holder
- Build Rack
- Secondary tray
- Stainless steel mesh



Interior



Oxygen concentration, temperature display



Nebulizer Sockets



LED lighting



Clean Air-filter



sliding window



detachable tray

- It provides a suitable environment for pets that need regular oxygen treatment, even at home
- An AI device controls the ventilation automatically creating a safe oxygen treatment environment
- An AI alarm system notifies you of oxygen deficiency
- Has automatic temperature control with a centralized heating method to help maintain body temperature
- An AI alarm system notifies you of temperature stranged
- Equipped with a dedicated nebulizer fan to enhance the effects of the treatment
- Clean Air-filter which removes indoor dust
- An easy-to-clean detachable tray and sliding window
- Five-stage adjustable internal LED lamp
- Reduces power consumption by up to 40%
- Soundproofing for sound-sensitive pets
- A holder can be attached for pets that need to have medical fluids administrated (option: Ringer holder)
- A secondary tray can be attached inside as a litter box for cats, a birthing box, etc. (option: Secondary tray)
- It is possible to stack machine which enable to provide space efficiency (option: Build Rack)

* This product requires a separate oxygen tank or oxygen concentrator or nebulizer.

CURADLE offers the best in luxury and Practicality

CURADLE SMART PET INCUBATOR

Care Cradle
RADLE



Animal Hospital



Curadle ICU 160 Core Functions

Smart GUI Touch Screen



7-inch touch screen for ease-of-use and operation

Reflecting Professional Vet Opinions



Reflects veterinarian's opinions taken at the product concept, leading to optimized design for actual medical situations

IR lamp, Internal light(LED), UVC lamp



Built-in are 3 different kinds of lamps, the LED lamp is to brighten inside, an infrared heating lamp and also the UV-C lamp to disinfect

Independent humidity system



Independent humidity system, which is easy to use and manage

Hand access




Hand access is to enable the pet treatment inside without opening the whole window

Stainless steel chamber




Stainless chamber to enhance durability designed helps sanitation management conveniently

Floor cooling/heating system, urine tray



Floor cooling/heating system, (PRO+ model) and urine tray designed to gather pet's urine in one place

Clean Air-filter



Built-in filter out dust and impurities. It can be used several times with dense filter material and it is easy to clean water



SMART PET INCUBATOR 160

PRO+ 160

- Veterinarian's opinions taken at the product concept
- Artificial intelligence electronic controller smartly controls the internal environment
- Automatic control and settings for temperature, humidity
- Can distinguish between the bottom temperature from air temperature, with a side heating feature and floor heating and cooling functions
- Control and setting of oxygen, carbon dioxide concentration
- Hand access is to enable the pet treatment inside without opening the whole window
- Built-in outlet to power external devices
- Stand pole to easily install peripheral devices
- Tempered glass view-window and one-touch door lock
- Sanitary stainless steel chamber and waste tray
- Washable Clean Air-Filter
- IR lamp, Internal light(LED), UVC lamp
- Large LCD screen, with quick buttons for temperature and multi language options
- Treatment time settings and alarm function
- Alarms in case of device abnormality
- Built-in IP camera to check real-time inside video on mobile (PX-ICU160C)

* This product requires a separate oxygen tank or oxygen concentrator.



Equipped with a large LCD screen with quick buttons for temperature and humidity control that ensures the right treatment for animal patients




Hand Access & Vent



IP Camera Application Model





SMART PET INCUBATOR 160



1 Home screen (PRO+)

7-inch touch screen for ease-of-use and operation

2 Settings screen (PRO+)

NEW interface where you can easily control every function

Select language by country
(English, German, Spanish, Portuguese,
Russian, Korean, Chinese, Japanese, Arabic)

PRO 160

- Veterinarian's opinions taken at the product concept
- Artificial intelligence electronic controller smartly controls the internal environment
- Automatic control and settings for temperature, humidity
- Can distinguish between the bottom temperature from air temperature, with a side heating feature and floor heating and cooling functions
- Control and setting of carbon dioxide concentration
- Hand access is to enable the pet treatment inside without opening the whole window
- Built-in outlet to power external devices
- Stand pole to easily install peripheral devices
- Tempered glass view-window and one-touch door lock
- Sanitary stainless steel chamber and waste tray
- Washable Clean Air-Filter
- IR lamp, Internal light(LED), UVC lamp
- Large LCD screen, with quick buttons and multi language options
- Treatment time settings and alarm function
- Alarms in case of device abnormality,

SPECIFICATION

Name	CURADLE SMART INCUBATOR PRO+ 160	CURADLE SMART INCUBATOR PRO 160
Model NO.	* for oxygen tank : PX-ICU160+(T) * for oxygen concentrator : PX-ICU160+(G) * for oxygen tank / IP camera included : PX-ICU160C(T) * for oxygen concentrator / IP camera included : PX-ICU160C(G)	PX-ICU160
Temp. control	MAX. 50°C / 122°F	
External environment temp.	Optimal range : 20 ~ 25°C / 68 ~ 77°F	
Humi. control	MAX. 70%	
External environment humi.	MAX. 60%	
Oxygen concentration Control	MAX. 40%	X
Oxygen Supply Pressure	Oxygen tank: 2 ~ 3bar / Oxygen concentrator: In case of below 6LPM, supply pressure doesn't matter. In case of more than 6LPM, 2 ~ 3bar	
Carbon dioxide concentration Control	MAX. 4000ppm	
Display	LCD (Touch Screen)	
Power	AC100-120V, 50/60Hz / AC220-240V, 50/60Hz	
Power consumption	Average: 95W	Average: 90W
size	External : W 916 x L 532 x H 768mm Internal : W 692 x L 470 x H 494mm / Capacity 160L	
Weight	57kg (N.W.) / 63kg (G.W)	56kg (N.W.) / 62kg (G.W)

* To improve the performance of the product, specifications are subject to change without prior notice.

Interior



Sold separately

- Ringer holder





The Greatest Life Creation with Superb Technique

CURADLE

HOW TO PLACE CURADLE



How to place 160 model

How to place 160 model & 90 model

To ensure ease of use and product safety, it is not recommended to load more than two levels of pet brooders.

SPECIFICATIONS BY PRODUCT



SPECIFICATIONS BY PET BROODER

Name		CURADLE PET BROODER 60	CURADLE PET BROODER 90	CURADLE PET O ₂ BROODER 90
Model NO.		MX-B60N	MX-B90N	MX-B90NO2
Temp. Control		Ambient temperature. ~ MAX. 38°C / ~ 100°F		
External Environment temp.		Optimal range : 20 ~ 25°C / 68 ~ 77°F		
Humi. Control		40 ~ 60% (It can be changed according to the conditions)		
External Environment humi.		40 ~ 60%		
Oxygen concentration Control		X	X	21, 25 ~ 40%
Oxygen Supply Pressure	Oxygen tank	X	X	1 ~ 1.5bar, MAX. 3bar
	Oxygen concentrator	X	X	In case of below 6LPM, supply pressure doesn't matter. In case of more than 6LPM, 1 ~ 1.5bar, MAX. 3bar
Display		FND		
Power		AC100-120V, 50/60Hz / AC220-240V, 50/60Hz		
Power consumption		Average: 80W / MAX: 150W	Average: 90W / MAX: 150W	Average: 90W / MAX: 150W
Size	External	W 655 x L 470 x H 440mm	W 855 x L 470 x H 440mm	W 855 x L 470 x H 440mm
	internal	W410 x L 430 x H 410mm / Capacity 60L	W 610 x L 430 x H 410mm / Capacity 90L	W 610 x L 430 x H 410mm / Capacity 90L
Weight		9kg	10kg	10kg
Sold separately		Build Rack, Secondary tray, Stainless steel mesh	Build Rack, Secondary tray, Stainless steel mesh	Ringer hold, Build Rack, Secondary, Stainless steel mesh

* Please consult with a veterinarian for oxygen generator settings and oxygen supply times.

* Pet brooder does not have cooling and dehumidification functions. If the temperature and humidity of the brooding room (the place where the brooder is installed) is higher than the brooder, the temperature and humidity cannot be lowered.

* To improve the performance of the product, specifications are subject to change without prior notice.



SPECIFICATIONS BY SMART PET INCUBATOR

Name		CURADLE SMART PET INCUBATOR PRO+ 160	CURADLE SMART PET INCUBATOR PRO 160
Model NO.		<ul style="list-style-type: none"> * for oxygen tank : PX-ICU160+(T) * for oxygen concentrator : PX-ICU160+(G) * for oxygen tank / IP camera included : PX-ICU160C(T) * for oxygen concentrator / IP camera included : PX-ICU160C(G) 	PX-ICU160
Temp. Control		MAX. 50℃ / ~ 122°F	
External Environment temp.		Optimal range : 20 ~ 25℃ / 68 ~ 77°F	
Humi. Control		MAX. 70%	
External Environment humi.		MAX. 60%	
Oxygen concentration Control		MAX. 40%	X
Oxygen Supply Pressure	Oxygen tank	2 ~ 3bar	
	Oxygen concentrator	In case of below 6LPM, supply pressure doesn't matter. In case of more than 6LPM, 2 ~ 3bar	
Carbon dioxide concentration Control		MAX. 4000ppm	
Display		LCD (Touch screen)	
Power		AC100-120V, 50/60Hz / AC220-240V, 50/60Hz	
Power consumption		Average: 95W	Average: 90W
Size	External	W 916 x L 532 x H 768mm	
	internal	W 692 x L 470 x H 494mm / Capacity 160L	
Weight		57kg (N.W.) / 63kg (G.W)	56kg (N.W.) / 62kg (G.W)
Sold separately		Ringer hold	



The Cradle of Pet Care, CURADLE

Manufacturer : Autoelex Co., Ltd
Head Office : 218, Sangdong-ro, Gimhae-si,
Gyeongsangnam-do, 50805 Korea
TEL. : +82-55-337-2561
FAX. : 055-337-2568
E-MAIL : sales@autoelex.com
Homepage : www.curadle.com



The Enterprise Loves the Nature, Human, and Life