

# GalaOxy C5 Series Oxygen Concentrator

## Safe Breath, Quality Life



Name	GalaOxy Oxygen Concentrator
Model	C5, C5T, and C5 PRO
Dimension	315mm (W) × 565mm (H) × 356mm (D)
Weight	20Kg
Oxygen Flow Rate	C5/C5T: 0-5 L/min; C5 PRO: 0-10 L/min (sync mode)
Flow Rate Accuracy	±10% or ±0.2 L/min (whichever is greater)
Oxygen Concentration	93%±3%
Modes	Continuous mode and sync mode (only for C5 PRO)
Noise	C5: ≤60dBA; C5T/C5 PRO: ≤45dBA
Timing Function	Timing range: 10 to 360 minutes; Adjustment increment: 10 minutes
Maximum Outlet Pressure	≥50 kPa (with the oxygen flow rate being 0)
Alarm	Abnormal Power Failure; Nasal Cannula Off; Low Oxygen Concentration; System Fault
Classification	Class II equipment; Type BF applied part; Not sterilized
Operating Conditions	Ambient temperature: 5°C to 40°C Relative humidity: ≤80%, non-condensing Pressure altitude: 86.0 kPa to 106.0 kPa
Storage and Shipping Conditions	Ambient temperature: -20°C to +55°C Relative humidity: ≤93%, non-condensing Pressure altitude: 70.0 kPa to 106.0 kPa



**MEDCAPTAIN MEDICAL TECHNOLOGY CO., LTD.**



Add: 12th Floor, Baiwang Research Building, No.5158 Shahe West Road,  
Xili, Nanshan, 518055 Shenzhen, Guangdong, PEOPLE'S REPUBLIC OF CHINA

Tel: +86 755 26953369

E-mail: [info@medcaptain.com](mailto:info@medcaptain.com)

Fax: +86 755 26001651

Website: [www.medcaptain.com](http://www.medcaptain.com)

MEDCAPTAIN is a trade mark of Medcaptain Medical Technology Co., Ltd.  
Specifications are subject to change without prior notice.

©2019 Medcaptain Medical Technology Co., Ltd. All rights reserved.

EN\_GalaOxyC5\_Datasheet\_V1.0\_20211101